

WETSUIT® ACCELERATOR - Part B for WETSUIT® 2-Part Waterproofing Membrane Professional Use Only

Contains CALCIUM CHLORIDE

DESCRIPTION

WETSUIT® Accelerator is a catalyst used in conjunction with the liquid-applied WETSUIT® 2-Part Waterproofing membrane.

RECOMMENDED USE

Wetsuit® Accelerator is designed to be used exclusively as catalyst with the Wetsuit® 2-Part waterproofing membrane.

PACKAGING / SHIPPING INFORMATION / STORAGE

WETSUIT® ACCELERATOR is supplied in bags. Product should be stored in dry and cool rooms.

Protect the material against moisture and direct sunlight.

Storage temperature: 5-30°C.

Shelf life 12 months

Products should remain in their original, unopened containers, bearing the manufacturers name, product designation, batch number and application precaution labels.

USE OF THE ACCELERATOR

One bag shall be mixed within a pail of 5 gallons of hot water to create enough accelerator to spray a full drum of Wetsuit 2-part.

Adjust the accelerator valve of the gun accordingly to ensure the right ratio. Between accelerator and wetsuit.

To our knowledge, all the technical information in this document is true and accurate at the date of publication of this technical data sheet and remain subject to modification without prior notice. The user can contact Neptune Coatings to verify the accuracy of the information before to specify the product or before to order it.

We warranty that our product are compliant with the standards of quality control established by Neptune Coatings. We don't accept any liability regarding the coverage ratio, the performances or any wound resulting from the use of the product. The responsibility of Neptune Coatings if any is limited to the replacement of the product. No other warranty is given by Neptune Coatings directly or indirectly, by legal route or otherwise, regarding the suitability of the product to a given application.